Foris HD aka Cut-X

Route

Construction	Tufted, Cut Pile
Face Fibre	ECONYL® 100% Recycled Nylon
Stain Resistance	Inherently stain resistant fibre
Finished Face Weight	875 g/m^2
Gauge	25,2 / 10 cm
Rows	37,5 / 10 cm
Tuft Density	94,488 /m^2
Finished Pile Height	5.8 mm
Standard Backing	WellBAC® Function Plus
Nominal Total Thickness	9.1 mm
Nominal Total Weight	4100 g/m^2
Tile Size	50 cm x 50 cm
Tiles per Box	20 (5m^2)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2018)	Class B_{fl} – s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 32 Suitable for high foot traffic
Castor Chair (BS EN 985:2001)	Class A – Intensive use (r value ≥ 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre

ENVIRONMENTAL

69% recycled content by total product weight

Manufactured in location certified to: ISO9001:2015 / ISO14001 / ISO45001 / ISO50001 using renewable electricity

M/PACT Carbon Offset Floors, 5.41 kg CO_2 e/m^2 Embodied Carbon (EPD calculation A1-A3) Cradle to Gate footprint 100% off set

WARRANTIES

10 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

INSTALLATION

Monolithic

CE

DOP-2895-1004-02
BS EN 14041