

MATERIAL SAFETY DATA SHEET

According to Regulation (EC) 1907/2006

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

Product Name: Vectair Airoma® Burst Hand Held Aerosol Air Freshener 750ml – Exotic Burst
Product Code: -
Application: SU22 Professional use. For industrial or institutional use. PC3 Air Freshener.
Supplier: Vectair Systems Ltd.
Unit 3, Trident Centre, Armstrong Road
Basingstoke, Hampshire RG24 8NU
Great Britain
E-mail: msds@vectair.co.uk
Website: www.vectair.co.uk

EMERGENCY TELEPHONE NUMBER, for DOCTORS/FIRE BRIGADE/POLICE only:
GB – Telephone: +44-1256-319500 (During office hours only)

EMERGENCY TELEPHONE NUMBER (for DOCTORS only):
National Poisons Information Service: +44-844 892 0111 (24/7)

2 HAZARD IDENTIFICATION

Classification: Extremely flammable.
CLP classification (GHS): Flammable aerosols, hazard category 1.
Human health hazards: Low hazard for usual industrial or commercial handling. Exposure to high vapour concentrations may result in a narcotic effect. Use only as directed. Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal. May produce an allergic reaction.
Physical/chemical hazards: Extremely flammable. Keep away from sources of ignition — No smoking. Do not spray on a naked flame or any incandescent material. Do not spray near fire, sources of heat or live electrical equipment. Aerosol may explode from internal pressure build-up when exposed to temperatures exceeding 50 °C.
Environmental hazards: Not classified as dangerous according to statutory EC-Directives.
Other information: Keep out of the reach of children. Caution: Do not breathe spray. Use only in well-ventilated areas. Spray in short intervals for a short period only. Ventilate well after use. Harmful to house pets.

Label elements (99/45/EC):
Hazard symbols:



F+: Extremely Flammable

R-and S-phrases: R12 Extremely flammable.
S2 Keep out of the reach of children.
S16 Keep away from sources of ignition — No smoking.
S23 Aerosol Do not breathe spray.
S51 Use only in well-ventilated areas.

MATERIAL SAFETY DATA SHEET

According to Regulation (EC) 1907/2006

Label elements (1272/2008/EC):

Hazard pictograms:



Signal word:

Danger

H-and P-phrases:

H222 Extremely flammable aerosol.
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Product Description: Mixture

Information on hazardous substances:

Substance name	Concentration (w/w) (%)	CAS nr.	EC nr.	Symbols	R-Phrases
Isobutane	50 – 75	75-28-5	200-857-2	F+	12
Ethanol	10 – 20	64-17-5	200-578-6	F	11
Propan-2-ol	5 – 10	67-63-0	200-661-7	F; Xi	11-36-67
Fragrance	<8	Mixture	Mixture		
Methanol	0.5 – 1	67-56-1	200-659-6	F	11
Butane	1 – 5	106-97-8	203-448-7	F+	12

Reference is made to chapter 16 for full text of each relevant R phrase. Occupational exposure limit(s), if relevant, are listed in section 8.

MATERIAL SAFETY DATA SHEET

According to Regulation (EC) 1907/2006

Substance Name	REACH No.	Hazard Class	Pictograms	H-phrases
Isobutane	01-2119485395-27	Flam.Gas.1; Press. Gas	GHS02; GHS04	H220
Ethanol	01-2119457610-43	Flam.Liq.2	GHS02	H225
Propan-2-ol	01-2119457558-25	Flam.Liq.2; Eye Irrit.2; STOT SE 3	GHS05; GHS07	H225; H319; H336
Fragrance	---	---	---	---
Methanol	01-2119433307-44	Flam. Liq. 2; Acute Tox. 3 (Dermal); Acute Tox. 3 (Inhalation); Acute Tox. 3 (Oral); STOT SE 1,	GHS02; GHS06; GHS08	H225; H331; H311; H301; H370; H225
Butane	---	Flam. Gas 1; Press. Gas	GHS02; GHS04	H220
Propane	---	Flam. Gas 1; Press. Gas	GHS02; GHS04	H220

Reference is made to chapter 16 for full text of each relevant H phrase.

4 FIRST-AID MEASURES

Effects and symptoms

Inhalation: No specific effects and/or symptoms are known.
Skin contact: May produce an allergic reaction. May cause dry skin and redness.
Eye contact: May cause stinging of eyes and redness.
Ingestion: Not applicable.

First aid measures

Inhalation: Not applicable under normal conditions of use. Consult a doctor if victim feels unwell.
Skin contact: Take off contaminated clothing. Wash off skin with plenty of water and soap before product dries up. Consult a doctor if irritation occurs.
Eye contact: Wash out with (lukewarm) water for at least 15 minutes. Remove contact lenses. Consult a doctor if irritation persists.
Ingestion: Not applicable.

5 FIRE-FIGHTING MEASURES

Extinguishing media

Suitable: Carbon dioxide (CO₂). Alcohol resistant foam. Dry chemical. Water fog.
Not suitable: Water jet.

Special exposure hazards:

Aerosol may explode from internal pressure build-up when exposed to temperatures exceeding 50 °C. Do not expose emergency personnel to overheated aerosol containers. Water may be used to cool container and prevent explosion of the aerosol.

Hazardous thermal decomposition products:

Carbon monoxide may be evolved if incomplete combustion occurs.

Special protective equipment for fire-fighters:

Fight a fire where aerosols are involved from a protected position. Use adequate respiratory equipment in case of insufficient ventilation.

MATERIAL SAFETY DATA SHEET

According to Regulation (EC) 1907/2006

6 ACCIDENTAL RELEASE MEASURES

Personal precautions:	Danger of slipping. Clean up spills immediately. Wear shoes with non-slip soles. Avoid contact with spilled or released material. See also section 8. Do not breathe vapours and/or spray. Keep away from sources of ignition — No smoking. Build up of highly flammable gasses involves an explosion risk. Vapours are heavier than air. Build up (of gasses) in low areas involves risk of suffocation.
Environmental precautions:	Avoid release of product into sewers, surface water and/or ground water. Waste product should not be allowed to contaminate soil or water.
Methods for cleaning up:	Collect spilled material in containers. Collect cans in an approved container. Do not pierce aerosols. Wash away remainder with plenty of water and soap.
Other information:	Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

7 HANDLING AND STORAGE

Handling:	Handle in accordance with good occupational hygiene and safety practices in well-ventilated areas. Important: Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Keep away from sources of ignition — No smoking. Do not spray on a naked flame or any incandescent material. Do not spray near fire, sources of heat or live electrical equipment. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Do not breathe spray. Avoid contact with skin and eyes.
Storage:	Keep frost-free, in a cool (< 35°), dry and well-ventilated place. Protect from sunlight and keep away from heat.
Recommended packaging:	Not applicable.
Use:	Use only as directed.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering measures:	Comply with standard precautionary measures for working with chemicals.
Hygienic measures:	When using do not eat, drink or smoke.
Occupational exposure limits:	Occupational exposure limits have not been established for this product.

Workplace exposure limits (mg/m³):

Chemical Name	Country	TWA 8 hour (mg/m ³)	STEL 15 min (mg/m ³)	Comments
Isobutane		1900		MAC: AU, CH, EE, FI
Ethanol	GB	1920	-	-
Propan-2-ol	GB	999	1250	-
Methanol	GB	266	333	-
Butane	GB	1450	1810	-

Personal protective equipment:

The efficiency of personal protective equipment depends among other things on temperature and degree of ventilation. Always get professional advice for the particular local situation.

MATERIAL SAFETY DATA SHEET

According to Regulation (EC) 1907/2006

Body protection:	Use of specific protective industrial clothing is not required under normal conditions of use. In case of large scale exposure wear suitable protective clothing, overalls or suit, and similar boots. Suitable material: nitril. Indication of permeation breakthrough time: not known.
Respiratory protection:	Take care of sufficient ventilation. Wear suitable respiratory protection in case of large scale exposure. Suitable: gas filter type A (brown), class I or higher on e.g. a facemask in accordance with EN 140.
Hand protection:	Under normal conditions of use specific gloves are not required. Wear special gloves in case of frequent or prolonged use and in case of large scale exposure. Suitable material: nitril. $\pm$ 0,5 mm Indication of permeation breakthrough time: not known.
Eye protection:	Wear appropriate safety glasses when there is danger of possible eye contact.

9 PHYSICAL AND CHEMICALS PROPERTIES

Appearance:	Aerosol.	
Colour:	Colourless.	
Odour:	Perfumed.	
Odour treshold:	Not known.	
pH:	Not applicable.	Almost waterfree product.
Solubility in water:	Soluble.	
Partition coefficient (n-octanol/water):	Not known.	
Flash point:	Not applicable.	Extremely flammable.
Auto ignition temperature:	>245 °C	
Boiling point/boiling range:	Not applicable.	
Melting point/melting range:	Not known.	
Explosion limits (in air):	Not known.	Lower explosion limit in air (%): 1,3 (Butane) Upper explosion limit in air (%): 19 (Ethanol)
Oxidising properties:	Not applicable.	Does not contain oxidizing substances.
Decomposition temperature:	Not applicable.	
Viscosity (20°C):	Not known.	
Viscosity (40°C):	Not known.	
Vapour pressure (20°C):	350000 Pa	
Vapour density (20°C):	Not known.	(air = 1)
Relative density (20°C):	0,65 g/ml	
Evaporation rate:	Not applicable.	(n-butyl acetate = 1)

10 STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to avoid:	Keep away from sources of ignition and sources of heat. See section 7.
Materials to avoid:	Not applicable.
Hazardous decomposition products:	Not known.
Reactivity:	No other hazardous reactions known.

11 TOXICOLOGICAL INFORMATION

MATERIAL SAFETY DATA SHEET

According to Regulation (EC) 1907/2006

No toxicological research has been carried out on this product.

Inhalation

Acute toxicity:	Calculated LC50: 10 mg/l. Ingredients of unknown toxicity: 6%. ATE: >5 mg/l. No specific effects and/or symptoms are known.
Corrosion/irritation:	May cause irritation to respiratory airways and coughing.
Sensitisation:	Not classified -based on available data, the classification criteria are not met.
Carcinogenicity:	Does not contain carcinogenic substances. Not classified -based on available data, the classification criteria are not met.
Mutagenicity:	Does not contain mutagenic substances. Not classified -based on available data, the classification criteria are not met.

Skin contact

Acute toxicity:	Calculated LD50: >5000 mg/kg.bw. Low toxicity. Not classified -based on available data, the classification criteria are not met.
Corrosion/irritation:	Slight irritation possible.
Sensitisation:	May produce an allergic reaction.
Mutagenicity:	Does not contain mutagenic substances. Not classified -based on available data, the classification criteria are not met.

Eye contact

Corrosion/irritation:	Slight irritation possible.
-----------------------	-----------------------------

Ingestion

Acute toxicity:	Aerosol/mist: Ingestion is unlikely to occur. Calculated LD50: >2738 mg/kg.bw. Low toxicity. Not classified -based on available data, the classification criteria are not met. May cause hampered eyesight.
Corrosion/irritation:	May cause a feeling of sickness, vomiting and diarrhoea.
Carcinogenicity:	Does not contain carcinogenic substances. Not classified -based on available data, the classification criteria are not met.
Mutagenicity:	Does not contain mutagenic substances. Not classified -based on available data, the classification criteria are not met.

12 ECOLOGICAL INFORMATION

No ecotoxicological research has been carried out on this product.

Ecotoxicity:	Not classified as dangerous for the aquatic environment.
Mobility:	Not applicable.
Persistence – degradability:	No specific information known.
Bioaccumulative potential:	No specific information known.
Other information:	Not applicable.

13 DISPOSAL CONSIDERATIONS

Product residues:	Recyclable metal container. Do not puncture or burn even after use. Do not dispose empty pack with regular household waste. Containers may be recycled. Treat product residues and non-empty pack as hazardous waste.
Additional warning:	Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.

MATERIAL SAFETY DATA SHEET

According to Regulation (EC) 1907/2006

European waste catalogue: Dispose hazardous waste in accordance with Directive 91/689/EEC under acknowledgement of a waste code according to Commission Decision 2000/532/EC to an official chemical waste depot.

Local legislation: Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

14 TRANSPORT INFORMATION

UN nr.: UN 1950
Transport name: AEROSOLS

ADR/RID (road / railway)

Class: 2
Classification code: 5F
Packaging group: -
Danger label: 2.1



:
IMDG (sea)
Class: 2
Packaging group: -
EmS(fire/spill): F-D/S-U
Marine pollutant: No

IATA (air)
Class: 2

Other information: Country specific variations may apply.

15 REGULATORY INFORMATION

Community regulations: Regulation (EC) No 1907/2006 (REACH), Regulation (EC) No 1272/2008 (CLP), 75/324/EEC (aerosols) and other regulations.

Additional labeling

Other information: The packaging shall carry the text: Important: Pressurized container protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition — No smoking. Keep out of the reach of children.

In the UK it is recommended that all aerosols should be labeled on the back with the warning about the dangers of volatile solvent abuse. The label should contain the badge 'Solvent Abuse Can Kill Instantly' accompanied by the phrase 'Use only as directed'.

MATERIAL SAFETY DATA SHEET

According to Regulation (EC) 1907/2006

16 OTHER INFORMATION

The information in this safety data sheet is compiled in compliance with Regulation (EC) 1907/2006 dated 18 December 2006 and accurate to the best of our knowledge and experience at the date of issue specified. It is the user's obligation to use this product safely and to comply with all applicable laws and regulations concerning the use of the product. This safety data sheet complements the technical information sheets but does not replace them and offers no warranty with regard to product properties.

Users are also forewarned for any hazards involved when the product is used for other purposes than those for which it is designed.

Changed or new information with regard to the previous release is indicated with an asterisk (*).

Full text of R-phrases mentioned in section 3:

- R11 Highly flammable.
- R12 Extremely flammable.
- R36 Irritating to eyes.
- R67 Vapours may cause drowsiness and dizziness.

Full text of H-phrases mentioned in section 3:

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

Number format : "," used as decimal separator.

History

Date of first issue: 05-03-2013